



This hydraulic auxiliary power unit works with all of our fishing products and is used on board ships equipped of outboard motors.

The standard hydraulic power pack, packaged in a sealed stainless steel tubular frame, consists of:

- a petrol or diesel ROBIN four stroke motor with an attached hydraulic pump.
- a stainless steel hydraulic tank, equipped with a back filter, a filler cap and a level indicator.
- a system of pressure adjustment and pressure control.

- ↪ **Installation:** simple to install and to use. It has a manual power starter.
- ↪ **Practical:** manometer for pressure monitoring with isolation valve.
- ↪ **Security:** pressure relief valve incorporated.
- ↪ **Stainless:** frame and hydraulic tank are in stainless steel.
- ↪ **Motor:** Robin four stroke motor, horizontal axis, mono-cylinder, air-cooled.

REF	Type	Motor	Power (in HP)	Flow (l/min)	Pressure max (bars)	Weight (in kg)	Measurement (LxWxH) in cm
712	GHE12	Petrol	4	9	130	33	56x40x43
717	GHE17	Petrol	6	16	130	45	60x45x50
723	GHD23	Diesel	4.8	16	130	56	60x45x50
727	GHD27	Diesel	5,5	19,8	120	57	62x45x50
725	GHE25	Petrol	8	21	150	65	73x51x55
742	GHD42	Diesel	8.5	24	150	87	73x51x55
<b>OTHER MODELS AVAILABLE ON REQUEST - UP TO 11HP</b>							

\* We reserve the rights to modify all components (shapes, sizes, etc) and product descriptions listed in our product sheets without prior notice.