

NETS TRANSPORTER



This equipment takes automatically the nets from the hauling area to the untying area whilst it is turning:

« PRODUCTIVITY IMPROVEMENT »

Enables to increase the speed of the turn. Unties nets whilst it is turning.

« IMPROVE THE WORKING CONDITIONS »

Gets rid off all manual pulling efforts.

« MULTI-PURPOSE USE »

Rotates at 180°
Simplify the process of nets loading.

❑ **Operation:** Traction system using auto-centred bands (**patented system**). Allows ropes Ø1mm to Ø12mm.

❑ **Installation:** The equipment glides onto a railing (not provided), made of two stainless steel tubes Ø 60mm, which are parallels (recommended height: 2 meters). This setup enables the nets removal from Port side to Starboard side and from Front to Back.

❑ **Practical:** a hydraulic distributor is incorporated on the nets transporter. It has a control lever: on/ off and is also used to regulate the speed.

❑ **Stainless:** built in stainless steel, aluminium and composite materials.

❑ **Light:** only 37kg.

REF	Pull (in kg)	Speed (m/min)	Flow (l/min)	Pressure (in bars)		Power (in HP)	Weight (in kg)
				Service	Max		
580	50	0 to 100	14	35	140	1,1	37

* We reserve the rights to modify all components (shapes, sizes, etc) and product descriptions listed in our product sheets without prior notice.